



Quick Reference Guide

EmbraceWAVE+ Blood Glucose Monitoring System




Understand Your New Meter



- METER DISPLAY**
Shows your blood glucose test results, memory values, averages, and other messages.
- ENTER**
Press and hold Enter (⏻) for 2 seconds to turn the meter on or off, or press Enter (⏻) to go into setup mode when not testing.
- (▲/▼) BUTTONS**
Press ▲ or ▼ to enter control mode with test strip inserted, during meter setup, or to navigate the stored test values and averages.
- TEST STRIP PORT**
This is where you insert the test strip and the meter will turn on automatically.
- BATTERY HOLDER**
Holds two CR 2032 3V Lithium coin cell batteries.

Understand Your New Meter



Understand Your New Meter



The batteries need to be inserted before using your meter for the first time or when "🔋" the icon appears on the meter display screen.

Houses CR2032 3V lithium coin cell batteries

- NOTE:**
- After changing the batteries, the meter automatically prompts you to check the time and date when it is turned on either by inserting a test strip or pressing "⏻". If it is correct, press "⏻" to confirm setup and exit, or if the time and date are not correct, turn to page 18 for Setting the Clock.
 - The stored results in memory will not be erased when the batteries are being changed.
 - Discard used batteries according to your local regulations.
 - The meter uses two CR2032 3V lithium coin cell batteries which can be found in most retail stores or on Amazon.com.
 - Always keep a spare package of batteries on hand.
 - Be sure the batteries go in + side up.
 - Remove the batteries if the meter is not used for a long period of time.

Setting Date and Time



- Press and hold "⏻" to turn on the meter.
- Press "▲" twice and the meter display screen shows "🕒".
- Press "⏻" and the current year will flash. Press "▲" or "▼" to select the correct year. Press "⏻" to confirm your choice.
- Advance to set the month, day, time format and time and press "⏻" to confirm your choice.

Testing Your Blood Glucose



- Insert a EmbraceWAVE Blood Glucose Test Strip to turn on the meter.
- Wait for the flashing blood drop and test strip icons to appear on the left of the meter display screen.
- Hold the lancing device against the side of your fingertip and press the release button to create a puncture.
- With the strip at a slight angle, touch the application area on the tip of the strip to the drop of blood, and the strip will draw the sample into the application area.
- The screen will start to count down. After 5 seconds, your glucose testing result will appear on the meter display screen.

- TIP:**
- Lance the side of your fingertip to avoid soreness. To avoid calluses, choose a different lancing site each time.

Viewing Stored Reading from Memory



- 1 Press and hold “**⏻**” to turn on the meter.




- 2 The flashing test strip icon will appear on the meter display screen.



- 3 Use “**▲**” or “**▼**” until meter display screen shows “**mem**” press “**⏻**” to confirm your choice.

- 4 The most recent test result will appear on screen. Press “**▲**” to view your results from the most recent to the oldest. When scrolling to the end of results in the memory, the meter display screen will show “**nil**”.



Upload Data via Bluetooth



- 1 To make a Bluetooth transfer, open the app on your mobile device and follow the app instructions to pairing the meter. The screen will show “Ent” and the Bluetooth icon “**⌘**” will flash.



- 2 Press “**⏻**” to pair with your mobile device.

- 3 When pairing is complete, the Bluetooth icon will stop flashing. Then the meter’s screen will show the blood glucose testing result.



- 4 Meter will start sending data to mobile device.

<https://www.health2sync.com/>



Download Health2Sync Diabetes Management here:

⚠️ WARNING:

- Data transmission via Bluetooth may decrease battery life.
- DO NOT pair another person’s meter with your mobile device. To pair the mobile device with your meter, follow the steps for uploading data via Bluetooth.

Problem Solving



- Damaged meter electronics or test strip**
- Replace the batteries and turn on the meter again.
 - Remove the test strip and insert a new test strip again.
 - If problem persists, call us at 1-877-979-5454 Monday through Friday from 9am to 5pm EST.



- Used or contaminated test strip**
- Remove the test strip and repeat the test with a new test strip.



- Not enough sample on the test strip to start the test**
- Remove the test strip and repeat the test with a new test strip. See Testing Your Blood Glucose on page 38.



- Removed test strip during countdown**
- Turn off the meter and repeat the test with a new test strip.



- Meter fails in Bluetooth status check**
- Replace the batteries and turn the meter on again.
 - If problem persists, call us at 1-877-979-5454 Monday through Friday from 9am to 5pm EST.

Problem Solving




- Bluetooth pairing failed**
- Check if mobile device is working properly and repeat confirm to pairing.
 - If problem persists, call us at 1-877-979-5454 Monday through Friday from 9am to 5pm EST



- Data transmission via Bluetooth failed**
- Do Not insert a new strip to replace current strip during data transmission



- Bluetooth disconnected between meter and mobile device during transmission procedure**
- Check if mobile device is working properly and repeat confirm to pairing and data transmission.



- Low battery**
- Change the batteries according to instructions for Changing the Batteries on page 17.



- Test result higher than 600 mg/dL**
- Wash and dry your hands and repeat the test on your fingertip with a new test strip. If the result is still “HI”, contact your physician or healthcare professional immediately.

Problem Solving



- Test result lower than 20 mg/dL**
- Wash and dry your hands and repeat the test on your fingertip with a new test strip. If the result is still “LO”, contact your physician or healthcare professional immediately.



- No results captured in the meter's memory**
- Check if the date and time on your meter is set up. See Setting Up Your New System on page 17.
 - Start testing your blood glucose, see Testing Your Blood Glucose on page 38.



- Temperature out of range**
- Move the meter into an area that is within 41°F~113°F, and allow 10 to 15 minutes for it to reach the new temperature.

⚠️ NOTE:

Please refer to the EmbraceWAVE+ instruction manual for more complete and detailed instructions and important safety warnings.

Contact Us

We're Here to Help.
If you have any questions about Embrace® products, please call us toll-free or visit our website.



1-877-979-5454
(Monday through Friday from 9am to 5pm EST)
www.OmnisHealth.com

[f /embracemeter](https://www.facebook.com/embracemeter) [@embracemeter](https://twitter.com/embracemeter)

- For In Vitro Diagnostic Use Only
- For Single-patient Use Only
- Suitable for Self-testing

Manufactured for:



1736 River Hills Drive, Suite 6
Nashville, TN 37210
www.OmnisHealth.com